

Specifications:

Fan size LxWxT	Bearing	Model	Rated Voltage	Start Voltage	Current	Speed	Air Flow	Static Pressure	Noise Level	Special					Weight
			VDC	VDC	Amp	rpm	CFM	mmH2O	dBA	Resistance Protection	Auto Start	Thermal Speed Control	Alarm Output	Tacho meter Output	
52x52x10 B	Sleeve	RDH5210S	12	6	0.14	6000	12.62	3.39	36.58	*	*			*	22
		RDM5210S			0.12	5000	10.37	2.47	31.94	*	*			*	
		RDL5210S			0.09	4000	8.31	1.64	26.16	*	*			*	
	Ball	RDH5210B			0.14	6000	12.62	3.39	36.58	*	*			*	
		RDM5210B			0.12	5000	10.37	2.47	31.94	*	*			*	
		RDL5210B			0.09	4000	8.31	1.64	26.16	*	*			*	
60x60x15 E	Sleeve	RDH6015S	12	6	0.12	4000	10.94	2.9	27.29	*	*			*	42
		RDM6015S			0.09	3200	8.54	1.92	21.63	*	*			*	
		RDL6015S			0.06	2500	6.39	1.2	18.54	*	*			*	
	Ball	RDH6015B			0.12	4000	10.94	2.9	27.29	*	*			*	
		RDM6015B			0.09	3200	8.54	1.92	21.63	*	*			*	
		RDL6015B			0.06	2500	6.39	1.2	18.54	*	*			*	
60x60x15 H	Sleeve	RDH6015S	12	6	0.17	4500	19.27	3.54	31.98	*	*			*	34
		RDM6015S			0.15	4000	16.6	2.9	28.94	*	*			*	
		RDL6015S			0.11	3500	14.6	2.24	26.1	*	*			*	
	Ball	RDH6015B			0.17	4500	19.27	3.54	31.98	*	*			*	
		RDM6015B			0.15	4000	16.6	2.9	28.94	*	*			*	
		RDL6015B			0.11	3500	14.6	2.24	26.1	*	*			*	
60x60x20 B	Sleeve	RDH6020S	12	6	0.16	4000	14.55	4.05	30.12	*	*	*	*	*	50
		RDM6020S			0.12	3300	11.86	2.73	24.69	*	*	*	*	*	
		RDL6020S			0.08	2500	6.84	1.59	19.43	*	*	*	*	*	
	Ball	RDH6020B			0.16	4000	14.55	4.05	30.7	*	*	*	*	*	
		RDM6020B			0.12	3300	11.86	2.73	25.5	*	*	*	*	*	
		RDL6020B			0.08	2500	8.64	1.59	19.68	*	*	*	*	*	
60x60x20 E	Sleeve	RDH6020S	12	6	0.16	4000	10.07	3.34	29.05	*	*	*	*	*	50
		RDM6020S			0.12	3300	8.35	2.32	24.02	*	*	*	*	*	
		RDL6020S			0.08	2500	5.99	1.34	19.58	*	*	*	*	*	
	Ball	RDH6020B			0.16	4000	10.07	3.34	31.8	*	*	*	*	*	
		RDM6020B			0.12	3300	8.35	2.32	26.36	*	*	*	*	*	
		RDL6020B			0.08	2500	5.99	1.34	20.64	*	*	*	*	*	
60x60x20 H	Sleeve	RDH6020S	12	6	0.16	4200	18.15	4.72	34.55	*	*	*	*	*	52
		RDM6020S			0.12	3500	16.2	3.22	28.41	*	*	*	*	*	
		RDL6020S			0.08	3000	12.39	2.3	24.2	*	*	*	*	*	
	Ball	RDH6020B			0.16	4200	18.15	4.72	34.55	*	*	*	*	*	
		RDM6020B			0.12	3500	16.2	3.22	28.41	*	*	*	*	*	
		RDL6020B			0.08	3000	12.39	2.3	24.2	*	*	*	*	*	
60x60x25 B	Sleeve	RDH6025S	12	6	0.14	4000	17.23	4.21	28.87	*	*	*	*	*	62
		RDM6025S			0.1	3000	12.65	2.51	21.73	*	*	*	*	*	
		RDL6025S			0.07	2500	10.55	1.72	19.71	*	*	*	*	*	
	Ball	RDH6025B			0.14	4000	17.23	4.21	28.87	*	*	*	*	*	
		RDM6025B			0.1	3000	12.65	2.51	21.73	*	*	*	*	*	
		RDL6025B			0.07	2500	10.55	1.72	19.71	*	*	*	*	*	