

Specifications:

Fan size LxWxT	Bearing	Model	Rated Voltage	Start Voltage	Current	Speed	Air Flow	Static Pressure	Noise Level	Special					Weight
			VDC	VDC	Amp	rpm	CFM	mmH2O	dBA	Resistance Protection	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output	g
90x90X25 C	Sleeve	RDH9025S	12	6	0.23	2800	34.01	2.25	35.22	*	*	*	*	*	75
		RDM9025S			0.19	2500	31.28	1.86	31.81	*	*	*	*	*	
		RDL9025S			0.16	2000	25.58	1.23	26.54	*	*	*	*	*	
	Ball	RDH9025B			0.23	2800	34.01	2.25	35.22	*	*	*	*	*	
		RDM9025B			0.19	2500	31.28	1.86	31.81	*	*	*	*	*	
		RDL9025B			0.16	2000	25.58	1.23	26.54	*	*	*	*	*	
90x90X25 H	Sleeve	RDH9025S	12	6	0.23	2800	48.11	3.19	34.5	*	*	*	*	*	85
		RDM9025S			0.19	2500	43.4	2.78	30.9	*	*	*	*	*	
		RDL9025S			0.16	2000	35.12	1.85	25.24	*	*	*	*	*	
	Ball	RDH9025B			0.23	2800	48.11	3.19	34.5	*	*	*	*	*	
		RDM9025B			0.19	2500	43.4	2.78	30.9	*	*	*	*	*	
		RDL9025B			0.16	2000	35.12	1.85	25.24	*	*	*	*	*	
120x120X25 B	Sleeve	RDH1225S	12	6	0.4	2400	69.15	3.82	39.96	*	*	*	*	*	164
		RDM1225S			0.23	2000	57.48	2.37	34.92	*	*	*	*	*	
		RDL1225S			0.18	1700	49.03	2.05	30.65	*	*	*	*	*	
	Ball	RDH1225B			0.4	2400	69.15	3.82	39.29	*	*	*	*	*	
		RDM1225B			0.23	2000	57.48	2.37	34.45	*	*	*	*	*	
		RDL1225B			0.18	1700	49.03	2.05	30.74	*	*	*	*	*	
120x120X32 B	Sleeve	RDH1232S	12	6	0.6	3750	120	10.1	49.8	*	*	*	*	*	250
		RDM1232S			0.5	3300	112	9.14	46.3	*	*	*	*	*	
		RDL1232S			0.32	2900	95	6.7	41.67	*	*	*	*	*	
	Ball	RDH1232B			0.6	3750	120	10.1	49.8	*	*	*	*	*	
		RDM1232B			0.5	3300	112	9.14	46.3	*	*	*	*	*	
		RDL1232B			0.32	2900	95	6.7	41.67	*	*	*	*	*	
	Sleeve	RDH1232S	24	12	0.45	3750	120	10.1	49.8	*	*	*	*	*	
		RDM1232S			0.28	3300	112	9.14	46.3	*	*	*	*	*	
		RDL1232S			0.22	2900	95	6.7	41.67	*	*	*	*	*	
		RDH1232B			0.45	3750	120	10.1	49.8	*	*	*	*	*	
	Ball	RDM1232B	0.28	3300	112	9.14	46.3	*	*	*	*	*			
		RDL1232B	0.22	2900	95	6.7	41.67	*	*	*	*	*			
Sleeve		RDH1232S	48	24	0.23	3750	120	10.1	49.8	*	*	*	*	*	
		RDM1232S			0.18	3300	112	9.14	46.3	*	*	*	*	*	
	RDL1232S	0.15			2900	95	6.7	41.67	*	*	*	*	*		
Ball	RDH1232B	0.23			3750	120	10.1	49.8	*	*	*	*	*		
	RDM1232B	0.18			3300	112	9.14	46.3	*	*	*	*	*		
	RDL1232B	0.15			2900	95	6.7	41.67	*	*	*	*	*		
120x120X38 B	Sleeve	RDH1238S	12	6	0.6	3000	121.29	8.11	44.71	*	*	*	*	*	266
		RDM1238S			0.6	2700	107.22	6.66	41.51	*	*	*	*	*	
		RDL1238S			0.4	2400	94.59	5.26	38.88	*	*	*	*	*	
		RDL1238S			0.25	2000	77.48	3.48	33.82	*	*	*	*	*	
	Ball	RDH1238B			0.6	3000	121.29	8.11	44.71	*	*	*	*	*	
		RDM1238B			0.6	2700	107.22	6.66	41.51	*	*	*	*	*	
		RDL1238B			0.4	2400	94.59	5.26	38.88	*	*	*	*	*	
		RDL1238B			0.25	2000	77.48	3.48	32.96	*	*	*	*	*	